

May. 2021



**SCC08GU03C2F1C-26V**  
**SCC16GU13C2F1C-26V**

**288-Pin DDR4 Unbuffered DIMM (X64, noECC)**  
**EU RoHS Compliant**

**Data Sheet**

**Rev. B**

Revision History		
Date	Revision	Subjects (major changes since last revision)
2021-05	A	Initial Release
2022-09	B	Optimize Module Description

**We Listen to Your Comments**

Any information within this document that you feel is wrong, unclear or missing at all? Your feedback will help us to continuously improve the quality of this document. Please send your proposal (including a reference to this document) to: [info@unisemicon.com](mailto:info@unisemicon.com)

# Contents

Contents.....	3
1 Overview.....	4
1.1 Features .....	4
1.2 Description .....	5
2 Pin Configurations.....	6
2.1 Pin Configurations .....	6
2.2 Pin Descriptions .....	8
3 General Description .....	11
3.1 General Description.....	11
3.2 Serial Presence-Detect EEPROM Operation .....	11
3.3 Function Block Diagram .....	12
3.4 DQ Map.....	14
4 Electrical Characteristics .....	16
4.1 Absolute Maximum Ratings .....	16
4.2 Operating Conditions .....	17
4.3 Module and Component Speed Grades .....	18
4.4 $I_{DD}/I_{PP}$ Specifications and Conditions .....	19
5 Package Dimensions .....	24
List of Figures.....	26
List of Tables .....	27

# 1 Overview

This chapter gives an overview of the 288-pin DDR4 UDIMM product family and describes its main characteristics.

## 1.1 Features

- 288-Pin PC4-2666 DDR4 UDIMM
- Frequency/CAS latency:  
0.75ns @ CL = 19 (DDR4-2666)
- VDD = 1.2V ±60mV
- VPP = 2.5V (2.375V~2.75V)
- VDDSPD = 2.5V
- Programmable CAS latency 9, 10,11, 12, 13, 14, 15  
16, 17, 18, 19 and 20 supported
- Programmable additive latency 0, CL-1, and CL-2  
supported (x4/x8 only)
- Programmable CAS Write latency (CWL) = 9, 10, 11, 12,  
14, 16,18
- Programmable burst length 4/8 with both nibble  
sequential and interleave mode
- Data bus inversion (DBI) for data bus
- Fly-by topology
- Terminated control command and address bus
- BL switch on the fly
- 16 internal banks; 4 groups of 4 banks each
- Nominal and dynamic on-die termination (ODT)  
for strobe, and mask signals
- Low-power auto self refresh (LPASR)
- On-die VREFDQ generation and calibration
- Fixed burst chop (BC) of 4 and burst length (BL)  
of 8 via the mode register set (MRS)
- Gold edge contacts
- Halogen-free
- Average Refresh Cycle (Tcase of 0 °C ~ 95 °C)  
- 7.8 µs at 0 °C ~ 85 °C  
- 3.9 µs at 85 °C ~ 95 °C

**Table 1 - Module Performance Table**

UnilC Speed Code		-26V	Unit	Note
DRAM Speed Grade	DDR4	-2666	MT/s	DRAM Speed Grade
CAS-RCD-RP latencies		19-19-19	t <sub>CK</sub>	
Min. RAS-CAS-Delay	t <sub>RCD</sub>	13.75	ns	
Min. Row Precharge Time	t <sub>RP</sub>	13.75	ns	
Min. Row Active Time	t <sub>RAS</sub>	32	ns	
Min. Row Cycle Time	t <sub>RC</sub>	45.75	ns	

## 1.2 Description

The UniC 8GB/16GB module family are DDR4 UDIMM with 31.25mm height based on DDR4 technology. DIMMs are intended for mounting into 288-pin connector sockets.

The memory array is designed with 8 Gbit Double-Data- Rate-Four (DDR4) Synchronous DRAMs. Decoupling capacitors are mounted on the PCB board. The DIMMs feature serial presence detect based on a serial E<sup>2</sup>PROM device using the 2-pin I<sup>2</sup>C protocol.



**Table 2 - Ordering Information**

Product Type <sup>1)</sup>	Compliance Code <sup>2)</sup>	Description	SDRAM Technology
SCC08GU03C2F1C-26V	8GB 1R×8 PC4-2666U-19-19-19	1Rank	8Gbit (×8)
SCC16GU13C2F1C-26V	16GB 2R×8 PC4-2666U-19-19-19	2Ranks	8Gbit (×8)

1) For detailed information regarding Product Type of UniC please see chapter "Product Type Nomenclature" of this data sheet.

2) This describes the speed grade, for example "PC4-2666U-19-19-19" where 2666 means DIMM modules with 2666MT/s data rate and "19-19-19" means Column Address Strobe (CAS) latency=19, Row Column Delay (RCD) latency = 19 and Row Precharge (RP) latency = 19.

**Table 3 - Address Format**

DIMM Density	8GB(1Rx8,X64)	16GB(2RX8,X64)
Row address	64K A[15:0]	64K A[15:0]
Column address	1K A[9:0]	1K A[9:0]
Device bank group address	4 BG[1:0]	4 BG[1:0]
Device bank address per group	4 BA[1:0]	4 BA[1:0]
Device configuration	8Gb(1G×8)	8Gb(1G×8)
Module rank address	1 CS <sub>n</sub> [0]	2CS <sub>n</sub> [1:0]
Device Quantity	8	16

## 2 Pin Configurations

### 2.1 Pin Configurations

The pin configuration of the 288-Pin DDR4 UDIMM is listed by function in **Table 4** (288 pins).

**Table 4 - Pin Configuration UDIMM (288 pin)**

Pin	Front	Pin	Back	Pin	Front	Pin	Back	Pin	Front	Pin	Back	Pin	Front	Pin	Back
1	NC	145	NC	39	VSS	183	DQ25	77	VTT	221	VTT	114	VSS	258	DQ47
2	VSS	146	VREFCA	40	DM3_n, DBI3_n, NC	184	VSS	KEY				115	DQ42	259	VSS
3	DQ4	147	VSS	41	NC	185	DQS3_c	78	EVENT_n	222	PARITY	116	VSS	260	DQ43
4	VSS	148	DQ5	42	VSS	186	DQS3_t	79	A0	223	VDD	117	DQ52	261	VSS
5	DQ0	149	VSS	43	DQ30	187	VSS	80	VDD	224	BA1	118	VSS	262	DQ53
6	VSS	150	DQ1	44	VSS	188	DQ31	81	BA0	225	A10/AP	119	DQ48	263	VSS
7	DM0_n, DBI0_n, NC	151	VSS	45	DQ26	189	VSS	82	RAS_n /A16	226	VDD	120	VSS	264	DQ49
8	NC	152	DQS0_c	46	VSS	190	DQ27	83	VDD	227	RFU	121	DM6_n, DBI6_n, NC	265	VSS
9	VSS	153	DQS0_t	47	NC	191	VSS	84	CS0_n	228	WE_n /A14	122	NC	266	DQS6_c
10	DQ6	154	VSS	48	VSS	192	NC	85	VDD	229	VDD	123	VSS	267	DQS6_t
11	VSS	155	DQ7	49	NC	193	VSS	86	CAS_n /A15	230	NC	124	DQ54	268	VSS
12	DQ2	156	VSS	50	VSS	194	NC	87	ODT0	231	VDD	125	VSS	269	DQ55
13	VSS	157	DQ3	51	DM8_n, DBI8_n, NC	195	VSS	88	VDD	232	A13	126	DQ50	270	VSS
14	DQ12	158	VSS	52	NC	196	NC	89	CS1_n	233	VDD	127	VSS	271	DQ51
15	VSS	159	DQ13	53	VSS	197	NC	90	VDD	234	NC	128	DQ60	272	VSS
16	DQ8	160	VSS	54	NC	198	VSS	91	ODT1	235	NC	129	VSS	273	DQ61
17	VSS	161	DQ9	55	VSS	199	NC	92	VDD	236	VDD	130	DQ56	274	VSS
18	DM1_n, DBI1_n, NC	162	VSS	56	NC	200	VSS	93	NC	237	NC	131	VSS	275	DQ57
19	NC	163	DQS1_c	57	VSS	201	NC	94	VSS	238	SA2	132	DM7_n, DBI7_n, NC	276	VSS
20	VSS	164	DQS1_t	58	RESET_n	202	VSS	95	DQ36	239	VSS	133	NC	277	DQS7_c

Pin	Front	Pin	Back	Pin	Front	Pin	Back	Pin	Front	Pin	Back	Pin	Front	Pin	Back
21	DQ14	165	VSS	59	VDD	203	CKE1	96	VSS	240	DQ37	134	VSS	278	DQS7_t
22	VSS	166	DQ15	60	CKE0	204	VDD	97	DQ32	241	VSS	135	DQ62	279	VSS
23	DQ10	167	VSS	61	VDD	205	RFU	98	VSS	242	DQ33	136	VSS	280	DQ63
24	VSS	168	DQ11	62	ACT_n	206	VDD	99	DM4_n, DBI4_n, NC	243	VSS	137	DQ58	281	VSS
25	DQ20	169	VSS	63	BG0	207	BG1	100	NC	244	DQS4_c	138	VSS	282	DQ59
26	VSS	170	DQ21	64	VDD	208	ALERT_n	101	VSS	245	DQS4_t	139	SA0	283	VSS
27	DQ16	171	VSS	65	A12 /BC_n	209	VDD	102	DQ38	246	VSS	140	SA1	284	VDDSPD
28	VSS	172	DQ17	66	A9	210	A11	103	VSS	247	DQ39	141	SCL	285	SDA
29	DM2_n, DBI2_n, NC	173	VSS	67	VDD	211	A7	104	DQ34	248	VSS	142	VPP	286	VPP
30	NC	174	DQS2_c	68	A8	212	VDD	105	VSS	249	DQ35	143	VPP	287	VPP
31	VSS	175	DQS2_t	69	A6	213	A5	106	DQ44	250	VSS	144	RFU	288	VPP
32	DQ22	176	VSS	70	VDD	214	A4	107	VSS	251	DQ45				
33	VSS	177	DQ23	71	A3	215	VDD	108	DQ40	252	VSS				
34	DQ18	178	VSS	72	A1	216	A2	109	VSS	253	DQ41				
35	VSS	179	DQ19	73	VDD	217	VDD	110	DM5_n, DBI5_n, NC	254	VSS				
36	DQ28	180	VSS	74	CK0_t	218	CK1_t	111	NC	255	DQS5_c				
37	VSS	181	DQ29	75	CK0_c	219	CK1_c	112	VSS	256	DQS5_t				
38	DQ24	182	VSS	76	VDD	220	VDD	113	DQ46	257	VSS				

## 2.2 Pin Descriptions

**Table 5 - Pin Descriptions**

Symbol	Type	Function
CKx_t, CKx_c,	Input	Clock: CK_t and CK_c are differential clock inputs. All address and control input signals are sampled on the crossing of the positive edge of CK_t and negative edge of CK_c.
CKEx	Input	Clock Enable: CKE HIGH activates and CKE LOW deactivates internal clock signals and device input buffers and output drivers. Taking CKE LOW provides Precharge Power-Down and Self-Refresh operation (all banks idle), or Active Power-Down (row Active in any bank). CKE is synchronous for Self-Refresh exit. After VREFCA and Internal DQ Vref have become stable during the power on and initialization sequence, they must be maintained during all operations (including Self-Refresh). CKE must be maintained high throughout read and write accesses. Input buffers, excluding CK_t, CK_c, ODT and CKE, are disabled during power-down. Input buffers, excluding CKE, are disabled during Self-Refresh.
CSx_n	Input	Chip Select: All commands are masked when CS-n is registered HIGH. CS_n provides for external Rank selection. CS_n is considered part of the command code.
Cx	Input	Chip ID : Chip ID is only used for 3DS for 2,4,8 high stack via TSV to select each slice of stacked component. Chip ID is considered part of the command code.
ODTx	Input	On Die Termination: ODT (registered HIGH) enables RTT_NOM termination resistance internal to the DDR4 SDRAM. When enabled, ODT is only applied to each DQ, DQS_t, DQS_c, TDQS_t and TDQS_c signal. The ODT pin will be ignored if MR1 is programmed to disable RTT_NOM.
ACT_n	Input	Activation Command Input: ACT_n defines the Activation command being entered along with CS_n. The input into RAS_n/A16, CAS_n/A15 and WE_n/A14 will be considered as Row Address A16, A15 and A14
RAS_n/A16. CAS_n/A15. WE_n/A14	Input	Command Inputs: RAS_n/A16, CAS_n/A15 and WE_n/A14 (along with CS_n) define the command being entered. Those pins have multi function. For example, for activation with ACT_n Low, these are Addresses like A16, A15 and A14 but for non-activation command with ACT_n High, these are Command pins for Read, Write and other command defined in command truth table
BGx	Input	Bank Group Inputs: BG0 - BG1 define which bank group an Active, Read, Write or Precharge command is being applied. BG0 also determines which mode register is to be accessed during a MRS cycle.
BAx	Input	Bank Address Inputs: BA0 - BA1 define to which bank an Active, Read, Write or Precharge command is being applied. Bank address also determines which mode register is to be accessed during a MRS cycle.
Ax	Input	Address Inputs: Provide the row address for ACTIVATE Commands and the column address for Read/Write commands to select one location out of the memory array in the respective bank. A10/AP, A12/BC_n, RAS_n/A16, CAS_n/A15 and WE_n/A14 have additional functions. See other rows. The address inputs also provide the op-code during Mode Register Set commands. A17 is only defined for 16 Gb x4 SDRAM configurations.
A10 / AP	Input	Auto-precharge: A10 is sampled during Read/Write commands to determine whether Autoprecharge should be performed to the accessed bank after the Read/Write operation. (HIGH: Autoprecharge; LOW: no Autoprecharge). A10 is sampled during a Precharge command to determine whether the Precharge applies to one bank (A10 LOW) or all banks (A10 HIGH). If only one bank is to be precharged, the bank is selected by bank addresses.



Symbol	Type	Function
A12/BC_n	Input	Burst Chop: A12/BC_n is sampled during Read and Write commands to determine if burst chop (on-the-fly) will be performed. (HIGH, no burst chop; LOW: burst chopped). See command truth table for details.
Parity	Input	Command and Address Parity Input: DDR4 Supports Even Parity check in SDRAMs with MR setting. Once it's enabled via Register in MR5, then SDRAM calculates Parity with ACT_n, RAS_n/A16, CAS_n/A15, WE_n/A14, BG0-BG1, BA0-BA1, A17-A0. Input parity should be maintained at the rising edge of the clock and at the same time with command & address with CS_n LOW
SAX	Input	Serial address inputs: Used to configure the temperature sensor/SPD EEPROM address range on the I2C bus.
SCL	Input	Serial clock for temperature sensor/SPD EEPROM: Used to synchronize communication to and from the temperature sensor/SPD EEPROM on the I2C bus.
RESET_n	CMOS Input	Active Low Asynchronous Reset: Reset is active when RESET_n is LOW, and inactive when RESET_n is HIGH. RESET_n must be HIGH during normal operation.
DQx, CBx	I/O	Data Input/ Output: Bi-directional data bus. If CRC is enabled via Mode register then CRC code is added at the end of Data Burst. Any DQ from DQ0-DQ3 may indicate the internal Vref level during test via Mode Register Setting MR4 A4=High. Refer to vendor specific data sheets to determine which DQ is used.
DQSx_t-DQSx_c	I/O	Data Strobe: output with read data, input with write data. Edge-aligned with read data, centered in write data. The data strobe DQS_t is paired with differential signals DQS_c, respectively, to provide differential pair signaling to the system during reads and writes. DDR4 SDRAM supports differential data strobe only and does not support single-ended.
DM_n/DBI_n/ TDQS_t (DMU_n, DBIU_n), (DML_n/ DBII_n)	I/O	Input data mask and data bus inversion: DM_n is an input mask signal for write data. Input data is masked when DM_n is sampled LOW coincident with that input data during a write access. DM_n is sampled on both edges of DQS. DM is multiplexed with the DBI function by the mode register A10, A11, and A12 settings in MR5. For a x8 device, the function of DM or TDQS is enabled by the mode register A11 setting in MR1. DBI_n is an input/output identifying whether to store/output the true or inverted data. If DBI_n is LOW, the data will be stored/ output after inversion inside the DDR4 device and not inverted if DBI_n is HIGH. TDQS is only supported in x8 SDRAM configurations (TDQS is not valid for UDIMMs).
SDA	I/O	Serial Data: Bidirectional signal used to transfer data in or out of the EEPROM or EEPROM/TS combo device.
ALERT_n	Output	Alert: It has multi functions such as CRC error flag, Command and Address Parity error flag as Output signal. If there is error in CRC, then ALERT_n goes LOW for the period time interval and goes back HIGH. If there is error in Command Address Parity Check, then ALERT_n goes LOW for relatively long period until ongoing SDRAM internal recovery transaction is complete. During Connectivity Test mode this pin functions as an input.
EVENT_n	Output	Temperature event: The EVENT_n pin is asserted by the temperature sensor when critical temperature thresholds have been exceeded. This pin has no function (NF) on modules without temperature sensors.

Symbol	Type	Function
TDQS_t TDQS_c (x8 DRAM-based RDIMM only)	Output	Termination data strobe: When enabled via the mode register, the DRAM device enables the same RTT termination resistance on TDQS_t and TDQS_c that is applied to DQS_t and DQS_c. When the TDQS function is disabled via the mode register, the DM/TDQS_t pin provides the data mask (DM) function, and the TDQS_c pin is not used. The TDQS function must be disabled in the mode register for both the x4 and x16 configurations. The DM function is supported only in x8 and x16 configurations. DM, DBI, and TDQS are a shared pin and are enabled/disabled by mode register settings. For more information about TDQS, see the DDR4 DRAM component datasheet (TDQS_t and TDQS_c are not valid for UDIMMs).
VDD	Supply	Module power supply: 1.2V (TYP).
VPP	Supply	DRAM activating power supply: 2.5V - 0.125V / +0.250V.
VREFCA	Supply	Reference voltage for control, command, and address pins.
VSS	Supply	Ground.
VTT	Supply	Power supply for termination of address, command, and control VDD/2.
VDDSPD	Supply	Power supply used to power the I2C bus for SPD.
RFU	-	Reserved for Future Use: No on DIMM electrical connection is present
NC	-	No Connect: No on DIMM electrical connection is present

## 3 General Description

### 3.1 General Description

High-speed DDR4 SDRAM modules use DDR4 SDRAM devices with 2 or 4 internal memory bank groups. DDR4 SDRAM modules utilizing 4- and 8-bit-wide DDR4 SDRAM have 4 internal bank groups consisting of 4 memory banks each, providing a total of 16 banks. Sixteen-bit-wide DDR4 SDRAM has 2 internal bank groups consisting of 4 memory banks each, providing a total of 8 banks. DDR4 SDRAM modules benefit from DDR4 SDRAM's use of an 8n-prefetch architecture with an interface designed to transfer two data words per clock cycle at the I/O pins. A single READ or WRITE operation for the DDR4 SDRAM effectively consists of a single 8n-bit-wide, four-clock data transfer at the internal DRAM core and eight corresponding n-bit wide, one-half-clock-cycle data transfers at the I/O pins.

DDR4 modules use two sets of differential signals: DQS, DQS# to capture data and CK and CK# to capture commands, addresses, and control signals. Differential clocks and data strobes ensure exceptional noise immunity for these signals and provide precise crossing points to capture input signals.

### 3.2 Serial Presence-Detect EEPROM Operation

DDR4 SDRAM modules incorporate serial presence-detect. The SPD data is stored in a 512-byte EEPROM. System READ/WRITE operations between the master (system logic) and the slave EEPROM device occur via a standard I2C bus using the DIMM's SCL (clock) SDA (data), and SA (address) pins. Write protect (WP) is connected to VSS, permanently disabling hardware write protection.

### 3.3 Function Block Diagram

Figure 1 – Function Block Diagram\_SCC08GU03C2F1C-26V





Figure 2 – Function Block Diagram\_SCC16GU13C2F1C-26V



### 3.4 DQ Map

Table 6 - DQ Map\_SCC08GU03C2F1C-26V

Module Pin NO.	Module DQ	Damping RES.	IC NO.	IC DQ	Module Pin NO.	Module DQ	Damping RES.	IC NO.	IC DQ
5	0	RN1(2-3)	U1	3	16	8	RN7(2-3)	U2	3
150	1	RN3(1-4)		1	161	9	RN5(1-4)		1
12	2	RN2(2-3)		2	23	10	RN8(2-3)		2
157	3	RN4(1-4)		0	168	11	RN6(1-4)		0
3	4	RN1(1-4)		7	14	12	RN7(1-4)		7
148	5	RN3(2-3)		5	159	13	RN5(2-3)		5
10	6	RN2(1-4)		6	21	14	RN8(1-4)		6
155	7	RN4(2-3)		4	166	15	RN6(2-3)		4
27	16	RN9(2-3)	U3	3	38	24	RN15(2-3)	U4	3
172	17	RN11(1-4)		1	183	25	RN13(1-4)		1
34	18	RN12(2-3)		2	45	26	RN14(2-3)		2
179	19	RN10(1-4)		0	190	27	RN16(1-4)		0
25	20	RN9(1-4)		7	36	28	RN15(1-4)		7
170	21	RN11(2-3)		5	181	29	RN13(2-3)		5
32	22	RN12(1-4)		6	43	30	RN14(1-4)		6
177	23	RN10(2-3)		4	188	31	RN16(2-3)		4
97	32	RN17(2-3)	U5	3	108	40	RN21(2-3)	U6	3
242	33	RN19(1-4)		1	253	41	RN23(1-4)		1
104	34	RN20(2-3)		2	115	42	RN24(2-3)		2
249	35	RN18(1-4)		0	260	43	RN22(1-4)		0
95	36	RN17(1-4)		7	106	44	RN21(1-4)		7
240	37	RN19(2-3)		5	251	45	RN23(2-3)		5
102	38	RN20(1-4)		6	113	46	RN24(1-4)		6
247	39	RN18(2-3)		4	258	47	RN22(2-3)		4
119	48	RN26(2-3)	U7	3	130	56	RN28(2-3)	U8	3
264	49	RN25(1-4)		1	275	57	RN30(1-4)		1
126	50	RN45(2-3)		2	137	58	RN29(2-3)		2
271	51	RN27(1-4)		0	282	59	RN31(1-4)		0
117	52	RN26(1-4)		7	128	60	RN28(1-4)		7
262	53	RN25(2-3)		5	273	61	RN30(2-3)		5
124	54	RN45(1_4)		6	135	62	RN29(1-4)		6
269	55	RN27(2-3)		4	280	63	RN31(2-3)		4

Table 7 - DQ Map\_SCC16GU13C2F1C-26V

Module Pin NO.	Module DQ NO.	Damping RES.	R0 IC NO.	R0 IC DQ	R1 IC NO.	R1 IC DQ	Module Pin NO.	Module DQ NO.	Damping RES.	R0 IC NO.	R0 IC DQ	R1 IC NO.	R1 IC DQ
5	0	R11	U1	3	U17	2	16	8	R16	U2	3	U16	2
150	1	R104		1		0	161	9	R98		1		0
12	2	R14		0		1	23	10	R19		2		3
157	3	R100		2		3	168	11	R94		0		1
3	4	R10		5		4	14	12	R15		7		6
148	5	R105		7		6	159	13	R99		5		4
10	6	R13		4		5	21	14	R18		6		7
155	7	R101		6		7	166	15	R95		4		5
27	16	R21	U3	1	U15	0	38	24	R26	U4	1	U14	0
172	17	R92		3		2	183	25	R86		3		2
34	18	R24		0		1	45	26	R29		2		3
179	19	R88		2		3	190	27	R82		0		1
25	20	R20		5		4	36	28	R25		7		6
170	21	R93		7		6	181	29	R87		5		4
32	22	R23		4		5	43	30	R28		6		7
177	23	R89		6		7	188	31	R83		4		5
97	32	R31	U6	7	U13	6	108	40	R36	U7	5	U12	4
242	33	R80		5		4	253	41	R74		7		6
104	34	R34		6		7	115	42	R39		4		5
249	35	R76		4		5	260	43	R70		6		7
95	36	R30		3		2	106	44	R35		1		0
240	37	R81		1		0	251	45	R75		3		2
102	38	R33		0		1	113	46	R38		2		3
247	39	R77		2		3	258	47	R71		0		1
119	48	R41	U8	5	U11	4	130	56	R46	U9	5	U10	4
264	49	R68		7		6	275	57	R62		7		6
126	50	R44		6		7	137	58	R49		4		5
271	51	R64		4		5	282	59	R58		6		7
117	52	R40		3		2	128	60	R45		1		0
262	53	R69		1		0	273	61	R63		3		2
124	54	R43		2		3	135	62	R48		2		3
269	55	R65		0		1	280	63	R59		0		1

## 4 Electrical Characteristics

This chapter contains speed grade definition, AC timing parameter and ODT tables.

### 4.1 Absolute Maximum Ratings

**Attention: Stresses greater than those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.**

**Table 8 - Absolute Maximum Ratings**

Symbol	Parameter	Rating		Unit	Note
		Min.	Max.		
$V_{DD}$	Voltage on $V_{DD}$ pin relative to $V_{SS}$	-0.4	+1.5	V	
$V_{DDQ}$	Voltage on $V_{DDQ}$ pin relative to $V_{SS}$	-0.4	+1.5	V	
$V_{PP}$	Voltage on $V_{PP}$ pin relative to $V_{SS}$	-0.4	3.0	V	
$V_{IN}, V_{OUT}$	Voltage on any pin relative to $V_{SS}$	-0.4	+1.5	V	
$T_{STG}$	Storage Temperature	-50	+100	°C	

Attention: Stresses above the max. values listed here may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. Maximum ratings are absolute ratings; exceeding only one of these values may cause irreversible damage to integrated circuit.

**Table 9 - DRAM Component Operating Temperature Range**

Symbol	Parameter	Rating		Unit	Note
		Min.	Max.		
$T_{CASE}$	Operating Temperature	0	95	°C	1)2)3)4)

- 1) Operating Temperature is the case surface temperature on the center / top side of the DRAM.
- 2) The operating temperature ranges are the temperatures where all DRAM specification will be supported. During operation, the DRAM case temperature must be maintained between 0 - 95 °C under all other specification parameters.
- 3) Above 85 °C the Auto-Refresh command interval has to be reduced to  $t_{REFI} = 3.9 \mu s$
- 4) When operating this product in the 85 °C to 95 °C  $T_{CASE}$  temperature range, the High Temperature Self Refresh has to be enabled by setting EMR(2) bit A7 to “1”.



## 4.2 Operating Conditions

**Table 10 - Supply Voltage Levels and AC / DC Operating Conditions**

Parameter	Symbol	Values			Unit	Note
		Min.	Typ.	Max.		
Device Supply Voltage	$V_{DD}$	1.14	1.2	1.26	V	1),2),3)
Output Supply Voltage	$V_{DDQ}$	1.14	1.2	1.26	V	1),2),3)
Peak-to-Peak Voltage	$V_{PP}$	2.375	2.5	2.75	V	3)
Input Reference Voltage	$V_{REF}$	$0.49 \times V_{DD}$	$0.5 \times V_{DDQ}$	$0.51 \times V_{DD}$	V	
DC Input Logic High	$V_{IH,CA}(DC65)$	$V_{REFCA} + 0.065$	—	$V_{DD}$	V	
DC Input Logic Low	$V_{IL,CA}(DC65)$	VSS	—	$V_{REFCA} - 0.065$	V	
AC Input Logic High	$V_{IH,CA}(AC90)$	$V_{REF} + 0.09$	—		V	
AC Input Logic Low	$V_{IL,CA}(AC90)$		—	$V_{REF} - 0.09$	V	

**Notes:**

- 1) Under all conditions VDDQ must be less than or equal to VDD.
- 2) VDDQ tracks with VDD. AC parameters are measured with VDD and VDDQ tied together.
- 3) DC bandwidth is limited to 20MHz.

## 4.3 Module and Component Speed Grades

DDR4 components may exceed the listed module speed grades; module may not be available in all listed speed grades

**Table 11 - Module and Component Speed Grades**

<b>Module Speed Grade</b>	<b>Component Speed Grade</b>
-26V	2666-19-19-19

## 4.4 I<sub>DD</sub>/I<sub>PP</sub> Specifications and Conditions

List of tables defining I<sub>DD</sub> / I<sub>PP</sub> Specifications and Conditions.

**Table 12 - I<sub>DD</sub> / I<sub>PP</sub> Measurement Conditions**

Symbol	Description
IDD0 IPP0	<p>Operating One Bank Active-Precharge Current (AL=0)</p> <p>CKE: High; External clock: On; tCK, nRC, nRAS, CL: Refer to Component Datasheet for detail pattern; BL: 8<sup>1</sup>; AL: 0; CS<sub>n</sub>: High between ACT and PRE; Command, Address, Bank Group Address, Bank Address Inputs: partially toggling; Data IO: VDDQ; DM<sub>n</sub>: stable at 1; Bank Activity: Cycling with one bank active at a time: 0,0,1,1,2,2,... ; Output Buffer and RTT: Enabled in Mode Registers<sup>2</sup>; ODT Signal: stable at 0; Pattern Details: Refer to Component Datasheet for detail pattern</p>
IDD1 IPP1	<p>Operating One Bank Active-Read-Precharge Current (AL=0)</p> <p>CKE: High; External clock: On; tCK, nRC, nRAS, nRCD, CL: Refer to Component Datasheet for detail pattern; BL: 8<sup>1</sup>; AL: 0; CS<sub>n</sub>: High between ACT, RD and PRE; Command, Address, Bank Group Address, Bank Address Inputs, Data IO: partially toggling; DM<sub>n</sub>: stable at 1; Bank Activity: Cycling with one bank active at a time: 0,0,1,1,2,2,... ; Output Buffer and RTT: Enabled in Mode Registers<sup>2</sup>; ODT Signal: stable at 0; Pattern Details: Refer to Component Datasheet for detail pattern</p>
IDD2N IPP2N	<p>Precharge Standby Current (AL=0)</p> <p>CKE: High; External clock: On; tCK, CL: Refer to Component Datasheet for detail pattern; BL: 8<sup>1</sup>; AL: 0; CS<sub>n</sub>: stable at 1; Command, Address, Bank Group Address, Bank Address Inputs: partially toggling ; Data IO: VDDQ; DM<sub>n</sub>: stable at 1; Bank Activity: all banks closed; Output Buffer and RTT: Enabled in Mode Registers<sup>2</sup>; ODT Signal: stable at 0; Pattern Details: Refer to Component Datasheet for detail pattern</p>
IDD2NT	<p>Precharge Standby ODT Current</p> <p>CKE: High; External clock: On; tCK, CL: Refer to Component Datasheet for detail pattern; BL: 8<sup>1</sup>; AL: 0; CS<sub>n</sub>: stable at 1; Command, Address, Bank Group Address, Bank Address Inputs: partially toggling ; Data IO: VSSQ; DM<sub>n</sub>: stable at 1; Bank Activity: all banks closed; Output Buffer and RTT: Enabled in Mode Registers<sup>2</sup>; ODT Signal: toggling according ; Pattern Details: Refer to Component Datasheet for detail pattern</p>
IDD2P IPP2P	<p>Precharge Power-Down Current CKE: Low; External clock: On; tCK, CL: Refer to Component Datasheet for detail pattern; BL: 8<sup>1</sup>; AL: 0; CS<sub>n</sub>: stable at 1; Command, Address, Bank Group Address, Bank Address Inputs: stable at 0; Data IO: VDDQ; DM<sub>n</sub>: stable at 1; Bank Activity: all banks closed; Output Buffer and RTT: Enabled in Mode Registers<sup>2</sup>; ODT Signal: stable at 0</p>
IDD2Q	<p>Precharge Quiet Standby Current</p> <p>CKE: High; External clock: On; tCK, CL: Refer to Component Datasheet for detail pattern; BL: 8<sup>1</sup>; AL: 0; CS<sub>n</sub>: stable at 1; Command, Address, Bank Group Address, Bank Address Inputs: stable at 0; Data IO: VDDQ; DM<sub>n</sub>: stable at 1; Bank Activity: all banks closed; Output Buffer and RTT: Enabled in Mode Registers<sup>2</sup>; ODT Signal: stable at 0</p>

Symbol	Description
IDD3N IPP3N	Active Standby Current  CKE: High; External clock: On; tCK, CL: Refer to Component Datasheet for detail pattern; BL: 8 <sup>1</sup> ; AL: 0; CS_n: stable at 1; Command, Address, Bank Group Address, Bank Address Inputs: partially toggling Data IO: VDDQ; DM_n: stable at 1; Bank Activity: all banks open; Output Buffer and RTT: Enabled in Mode Registers <sup>2</sup> ; ODT Signal: stable at 0; Pattern Details: Refer to Component Datasheet for detail pattern
IDD3P IPP3P	Active Power-Down Current  CKE: Low; External clock: On; tCK, CL: Refer to Component Datasheet for detail pattern; BL: 8 <sup>1</sup> ; AL: 0; CS_n: stable at 1; Command, Address, Bank Group Address, Bank Address Inputs: stable at 0; Data IO: VDDQ; DM_n: stable at 1; Bank Activity: all banks open; Output Buffer and RTT: Enabled in Mode Registers <sup>2</sup> ; ODT Signal: stable at 0
IDD4R IPP4R	Operating Burst Read Current  CKE: High; External clock: On; tCK, CL: Refer to Component Datasheet for detail pattern; BL: 8 <sup>2</sup> ; AL: 0; CS_n: High between RD; Command, Address, Bank Group Address, Bank Address Inputs: partially toggling ; Data IO: seamless read data burst with different data between one burst and the next one according ; DM_n: stable at 1; Bank Activity: all banks open, RD commands cycling through banks: 0,0,1,1,2,2,... ; Output Buffer and RTT: Enabled in Mode Registers <sup>2</sup> ; ODT Signal: stable at 0; Pattern Details: Refer to Component Datasheet for detail pattern
IDD4W IPP4W	Operating Burst Write Current  CKE: High; External clock: On; tCK, CL: Refer to Component Datasheet for detail pattern; BL: 8 <sup>1</sup> ; AL: 0; CS_n: High between WR; Command, Address, Bank Group Address, Bank Address Inputs: partially toggling ; Data IO: seamless write data burst with different data between one burst and the next one ; DM_n: stable at 1; Bank Activity: all banks open, WR commands cycling through banks: 0,0,1,1,2,2,... ; Output Buffer and RTT: Enabled in Mode Registers <sup>2</sup> ; ODT Signal: stable at HIGH; Pattern Details: Refer to Component Datasheet for detail pattern
IDD5B IPP5B	Burst Refresh Current (1X REF)  CKE: High; External clock: On; tCK, CL, nRFC: Refer to Component Datasheet for detail pattern; BL: 8 <sup>1</sup> ; AL: 0; CS_n: High between REF; Command, Address, Bank Group Address, Bank Address Inputs: partially toggling ; Data IO: VDDQ; DM_n: stable at 1; Bank Activity: REF command every nRFC ; Output Buffer and RTT: Enabled in Mode Registers <sup>2</sup> ; ODT Signal: stable at 0; Pattern Details: Refer to Component Datasheet for detail pattern
IDD5F2 IPP5F2	Burst Refresh Current (2X REF) tRFC=tRFC_x2,
IDD5F4 IPP5F4	Burst Refresh Current (4X REF) tRFC=tRFC_x4,
IDD6N IPP6N	Self Refresh Current: Normal Temperature Range  Tcase: 0 - 85°C; Low Power Array Self Refresh (LP ASR) : Normal <sup>4</sup> ; CKE: Low; External clock: Off; CK_t and CK_c#: LOW; CL: Refer to Component Datasheet for detail pattern; BL: 8 <sup>1</sup> ; AL: 0; CS_n#, Command, Address, Bank Group Address, Bank Address, Data IO: High; DM_n: stable at 1; Bank Activity: Self-Refresh operation; Output Buffer and RTT: Enabled in Mode Registers <sup>2</sup> ; ODT Signal: MIDDLELEVEL
IDD6E IPP6E	Self-Refresh Current: Extended Temperature Range)  TCase: 0 - 95°C; Low Power Array Self Refresh (LP ASR) : Extended <sup>4</sup> ; CKE: Low; External clock: Off; CK_t and CK_c: LOW; CL: Refer to Component Datasheet for detail pattern; BL: 8 <sup>1</sup> ; AL: 0; CS_n, Command, Address, Bank Group Address, Bank Address, Data IO: High; DM_n: stable at 1; Bank Activity: Extended Temperature Self-Refresh operation; Output Buffer and RTT: Enabled in Mode Registers <sup>2</sup> ; ODT Signal: MID-LEVEL

Symbol	Description
IDD6R IPP6R	Self-Refresh Current: Reduced Temperature Range  TCASE: 0 - 45°C; Low Power Array Self Refresh (LP ASR) : Reduced <sup>4</sup> ; CKE: Low; External clock: Off; CK_t and CK_c#: LOW; CL: Refer to Component Datasheet for detail pattern; BL: 8 <sup>1</sup> ; AL: 0; CS_n#, Command, Address, Bank Group Address, Bank Address, Data IO: High; DM_n:stable at 1; Bank Activity: Extended Temperature Self-Refresh operation; Output Buffer and RTT: Enabled in Mode Registers <sup>2</sup> ; ODT Signal: MID-LEVEL
IDD6A IPP6A	Auto Self-Refresh Current  TCASE: 0 - 95°C; Low Power Array Self Refresh (LP ASR) : Auto <sup>4</sup> ; CKE: Low; External clock: Off; CK_t and CK_c#: LOW; CL: Refer to Component Datasheet for detail pattern; BL: 8 <sup>1</sup> ; AL: 0; CS_n#, Command, Address, Bank Group Address, Bank Address, Data IO: High; DM_n:stable at 1; Bank Activity: Auto Self-Refresh operation; Output Buffer and RTT: Enabled in Mode Registers <sup>2</sup> ; ODT Signal: MID-LEVEL
IDD7 IPP7	Operating Bank Interleave Read Current  CKE: High; External clock: On; tCK, nRC, nRAS, nRCD, nRRD, nFAW, CL: Refer to Component Datasheet for detail pattern; BL: 8 <sup>1</sup> ; AL: CL-1; CS_n: High between ACT and RDA; Command, Address, Bank Group Address, Bank Address Inputs: partially toggling ; Data IO: read data bursts with different data between one burst and the next one ; DM_n: stable at 1; Bank Activity: two times interleaved cycling through banks (0, 1, ...7) with different addressing; Output Buffer and RTT: Enabled in Mode Registers <sup>2</sup> ; ODT Signal: stable at 0; Pattern Details: Refer to Component Datasheet for detail pattern
IDD8 IPP8	Maximum Power Down Current TBD

**Notes :**

1. Burst Length: BL8 fixed by MRS: set MR0 [A1:0=00].
2. Output Buffer Enable - set MR1 [A12 = 0] : Qoff = Output buffer enabled - set MR1 [A2:1 = 00] : Output Driver Impedance Control = RZQ/7  
 RTT\_Nom enable - set MR1 [A10:8 = 011] : RTT\_NOM = RZQ/6 RTT\_WR enable - set MR2 [A10:9 = 01] : RTT\_WR = RZQ/2 RTT\_PARK  
 disable - set MR5 [A8:6 = 000]
3. CAL enabled : set MR4 [A8:6 = 001] : 1600MT/s 010] : 1866MT/s, 2133MT/s 011] : 2400MT/s Gear Down mode enabled :set MR3 [A3 = 1] :  
 1/4 Rate DLL disabled : set MR1 [A0 = 0] CA parity enabled :set MR5 [A2:0 = 001] : 1600MT/s,1866MT/s, 2133MT/s 010] : 2400MT/s Read  
 DBI enabled : set MR5 [A12 = 1] Write DBI enabled : set :MR5 [A11 = 1]
4. Low Power Array Self Refresh (LP ASR) : set MR2 [A7:6 = 00] : Normal 01] : Reduced Temperature range 10] : Extended Temperature  
 range 11] : Auto Self Refresh

**Table 13 - IDD Specification for SCC08GU03C2F1C-26V and SCC16GU13C2F1C-26V**

Product Type	SCC08GU03C2F1C-26V	SCC16GU13C2F1C-26V	Unit	Note
Organization	8GB	16GB		
	1 Rank (×8)	2Rank (×8)		
	×64	×64		
	-26V	-26V		
Symbol	Current	Current		
IDD0	695.2	1053	mA	2)
IDD1	832	1190	mA	2)
IDD2N	531.2	1062	mA	3)
IDD2NT	597.6	955.2	mA	2)
IDD2P	357.6	715.2	mA	3)
IDD2Q	488.8	977.6	mA	3)
IDD3N	568	1136	mA	3)
IDD3P	372.8	745.6	mA	3)
IDD4R	1263	1621	mA	2)
IDD4W	1344	1702	mA	2)
IDD5B	2286	2644	mA	2)
IDD6N	318.4	636.8	mA	3)
IDD6E	402.4	804.8	mA	3)
IDD6R	256	512	mA	3)
IDD6A	402.4	804.8	mA	3)
IDD7	1981	2338	mA	2)
IDD8	247.2	494.4	mA	3)

- 1) Calculated values from Device data.
- 2) One module rank in the active IDD/IPP, the other rank in IDD2P/IPP3N.
- 3) All ranks in this IDD/IPP condition

**Table 14 - I<sub>PP</sub> Specification for SCC08GU03C2F1C-26V and SCC16GU13C2F1C-26V**

Product Type	SCC08GU03C2F1C-26V	SCC16GU13C2F1C-26V	Unit	Note
Organization	8GB	16GB		
	1 Rank (×8)	2Rank (×8)		
	×64	×64		
	-26V	-26V		
Symbol	Current	Current		
IPP0	63.2	90.4	mA	2)
IPP1	63.2	90.4	mA	2)
IPP2N	27.2	54.4	mA	3)
IPP3N	27.2	54.4	mA	3)
IPP5B	290.4	317.6	mA	2)
IPP6N	42.4	84.8	mA	3)
IPP7	213.6	240.8	mA	2)

- 1) Calculated values from Device data.
- 2) One module rank in the active IDD/IPP, the other rank in IDD2P/IPP3N.
- 3) All ranks in this IDD/IPP condition







## List of Figures

Figure 1 – Function Block Diagram_SCC08GU03C2F1C-26V .....	12
Figure 2 – Function Block Diagram_SCC16GU13C2F1C-26V .....	13
Figure 3 - Package Dimensions_SCC08GU03C2F1C-26V.....	24
Figure 4 - Package Dimensions_SCC16GU13C2F1C-26V.....	25

## List of Tables

Table 1 - Module Performance Table.....	4
Table 2 - Ordering Information.....	5
Table 3 - Address Format .....	5
Table 4 - Pin Configuration UDIMM (288 pin).....	6
Table 5 - Pin Descriptions.....	8
Table 6 - DQ Map_SCC08GU03C2F1C-26V .....	14
Table 7 - DQ Map_SCC16GU13C2F1C-26V .....	15
Table 8 - Absolute Maximum Ratings .....	16
Table 9 - DRAM Component Operating Temperature Range .....	16
Table 10 - Supply Voltage Levels and AC / DC Operating Conditions .....	17
Table 11 - Module and Component Speed Grades.....	18
Table 12 - I <sub>DD</sub> /I <sub>PP</sub> Measurement Conditions .....	19
Table 13 - I <sub>DD</sub> Specification for SCC08GU03C2F1C-26V and SCC16GU13C2F1C-26V .....	22
Table 14 - I <sub>PP</sub> Specification for SCC08GU03C2F1C-26V and SCC16GU13C2F1C-26V.....	23

**Edition 2020-06**  
**Published by**  
**Xi'an UnilC Semiconductors Co., Ltd.**

**Xi'an: 4th Floor, Building A,**  
**No. 38 Gaoxin 6th Road,**  
**Xian High-tech Industries Development Zone**  
**Xi'an, Shaanxi 710075, P. R. China**  
**Tel: +86-29-88318000**  
**Fax: +86-29-88453299**

**info@unisemicon.com**

**© UnilC 2020.**  
**All Rights Reserved.**

#### **Legal Disclaimer**

THE INFORMATION GIVEN IN THIS INTERNET DATA SHEET SHALL IN NO EVENT BE REGARDED AS A GUARANTEE OF CONDITIONS OR CHARACTERISTICS. WITH RESPECT TO ANY EXAMPLES OR HINTS GIVEN HEREIN, ANY TYPICAL VALUES STATED HEREIN AND/OR ANY INFORMATION REGARDING THE APPLICATION OF THE DEVICE, UNILC HEREBY DISCLAIMS ANY AND ALL WARRANTIES AND LIABILITIES OF ANY KIND, INCLUDING WITHOUT LIMITATION WARRANTIES OF NON-INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS OF ANY THIRD PARTY.

#### **Information**

For further information on technology, delivery terms and conditions and prices please contact your nearest UnilC Office.

#### **Warnings**

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest UnilC Office.

UnilC Components may only be used in life-support devices or systems with the express written approval of UnilC, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

[www.unisemicon.com](http://www.unisemicon.com)